



PKG-SYS INC.

1808-28

Compact Shrink Tunnel



Specifications

- Tunnel opening: 28" L × 18" W × 8" H
- Conveyor speed: 0–75 FPM
- Power: 220V / 1 phase / 40 amps
- Machine dimensions: 40" L × 26" W × 61" H
- Weight: 450 lb

Overview

The 1808-28 Shrink Tunnel is a general-purpose solution designed for a wide range of applications, including shrink bands, neck bands, full-body sleeves, shrink film, and drying or curing processes. Built for reliable, consistent performance, it integrates easily into a variety of packaging lines and production environments.

Features

- Fully recirculating hot air chamber for uniform shrink results
- Digital temperature control up to 400°F
- Adjustable air velocity for consistent, precise shrink performance
- AC variable-speed drive with conveyor speeds from 0–75 FPM
- Heavy-duty live roller rod conveyor
- Fast heat-up with 7.5 kW heater bank (300°F in under 15 minutes)
- Quiet, production-friendly operation
- Chromed, rust-resistant conveyor rollers and shafts
- Automatic tunnel cool-down with safety shutoff
- 2-year warranty

Options

- 12" tunnel opening
- High-density rollers with tight ½" spacing
- Teflon® mesh conveyor belt
- Stainless steel metal mesh conveyor belt

Contact us: robert@pkg-sys.com | (760) 594-1345

WWW.PKG-SYS.COM