



PKG-SYS INC.

# 1622MK-Combo

## Shrink Packaging System



### Specifications

- Seal Size: 16" W × 22" L
- Tunnel Opening: 28" L × 18" W × 8" H
- Max Film Width: 20"
- Electrical: 220 V, 1 Phase, 45 Amps, 50/60 Hz
- Machine Dimensions: 103" L × 32" W × 62" H
- Weight: 1,150 lbs

### Overview

The 1622MK-Combo is an integrated semi-automatic L-sealer and shrink tunnel system built on a single frame for smooth product flow and efficient operation. Designed for flexibility and consistent results, the system allows operators to easily align products from seal to shrink while maintaining a compact footprint.

Ideal for a wide range of package sizes and film types, the 1622MK-Combo delivers dependable performance for growing production environments. With reliable throughput and straightforward setup, it's a practical solution for operations that need professional shrink packaging without unnecessary complexity.

### Features

- Micro-Knife Seal Technology
- 16" W × 22" L Seal Area
- Linear Bearing Sealer Adjustment (Forward/Backward)
- Power Discharge Conveyor
- Easy-Load Film Cradle with Brake
- Single Power Source
- Fully Re-Circulating Air Chamber
- Live Roller Rod Conveyor
- Digital Temperature Control
- Variable Speed Drive & Air Velocity Control
- Fast Heat-Up (Up to 300°F in Under 10 Minutes)
- Adjustable Tunnel Height

Contact us: [robert@pkg-sys.com](mailto:robert@pkg-sys.com) | (760) 594-1345

[WWW.PKG-SYS.COM](http://WWW.PKG-SYS.COM)