



PKG-SYS INC.

2028W

Heavy-Duty Wire L-Sealer



Contact us: robert@pkg-sys.com | (760) 594-1345

WWW.PKG-SYS.COM

Overview

The 2028W L-Sealer is built for dependable, high-output packaging. Its 20" × 28" seal area, heavy-duty construction, and cast aluminum seal head with Nichrome wire sealing deliver fast, consistent results in demanding production environments. Designed for continuous operation, it runs at 10–15 packages per minute with long-term reliability and minimal upkeep.

Features

- .036 Nichrome wire seal for clean, consistent seals
- Motorized discharge conveyor for smooth, continuous product flow
- Stainless steel compensator to maintain even sealing pressure
- Dual magnet hold-down system for secure, repeatable seals
- Adjustable seal and conveyor timers for precise cycle control
- Film roll guides and brake to keep film aligned and prevent over-feeding
- Pin wheel hole punch for controlled air release
- Locking casters for easy positioning and stability

Specifications

- Power: 220 V, 1 Phase, 20 Amps
- Weight: 570 lb (net) / 640 lb (shipping)
- Seal Area: 20" W × 28" L
- Maximum Film Width: 25"
- Machine Dimensions: 81" L × 32" W × 39" H
- Footprint: approx. 18 sq ft